

SYNTHETIC BLEND MOTOR OIL

(API SP, ILSAC GF-6A)

SAE 5W-20 / 5W-30



TYPICAL PROPERTIES

PASSENGER CAR MOTOR OIL	SAE	5W-20	5W-30
API Service		SP	SP
ILSAC		GF-6A	GF-6A
Kinematic Viscosity cSt @ 40°C cSt @ 100°C		50.0 8.6	62.1 10.4
Viscosity Index		150	157
CCS Viscosity cP @ -30°C		6000	6300
Evaporative Loss, NOACK, wt%		<15	<15
Specific Gravity 15.6°C (60°F)		0.862	0.861
Flash Point, °C		218	220
Pour Point, °C		-39	-39
Color (ASTM)		3.0	3.0
Sulfated Ash, wt%		0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

MERIT Synthetic Blend Passenger Car Motor Oils

are specially formulated with a combination of Group II and Group III base oils plus state-of-the-art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20 and 5W-30 grades are Resource Conserving motor oils that exceed API service SP, and ILSAC GF-6A, as well as older service categories SN PLUS, SM, SL, and previous ILSAC categories.



DON'T POLLUTE • CONSERVE RESOURCES • RETURN USED OIL TO COLLECTION CENTERS

Deckman Oil Co., Inc.

Honeoye Falls, New York 14472

(800) 836-0562



SYNTHETIC BLEND MOTOR OIL

(API SP, ILSAC GF-6A)

SAE 5W-20 / 5W-30